




## MBR0540

### Features

- 0.5 ampere; forward voltage less than 460 mv.
- 400 milliwatt Power Dissipation package.
- Compact surface mount package with same footprint as mini-melf.



**SOD123**  
Color Band Denotes Cathode  
Mark: B4

## Schottky Rectifiers

### Absolute Maximum Ratings\*

$T_A = 25^\circ\text{C}$  unless otherwise noted

| Symbol      | Parameter                                                                   | Value       | Units            |
|-------------|-----------------------------------------------------------------------------|-------------|------------------|
| $V_{RRM}$   | Maximum Repetitive Reverse Voltage                                          | 40          | V                |
| $I_{F(AV)}$ | Average Rectified Forward Current                                           | 500         | mA               |
| $I_{FSM}$   | Non-repetitive Peak Forward Surge Current<br>half wave, single phase, 60 Hz | 5.5         | A                |
| $T_{stg}$   | Storage Temperature Range                                                   | -65 to +150 | $^\circ\text{C}$ |
| $T_J$       | Operating Junction Temperature                                              | -65 to +125 | $^\circ\text{C}$ |

\*These ratings are limiting values above which the serviceability of any semiconductor device may be impaired.

### Thermal Characteristics

| Symbol          | Parameter                                 | Value | Units              |
|-----------------|-------------------------------------------|-------|--------------------|
| $R_{\theta JA}$ | Thermal Resistance, Junction to Ambient * | 206   | $^\circ\text{C/W}$ |
| $R_{\theta JL}$ | Thermal Resistance, Junction to Lead **   | 118   | $^\circ\text{C/W}$ |

\*1.0 inch" pad size (1.0 x 0.5 inch for each lead) on FR4 board.

\*\*Device mounted on FR-4 PCB 0.013 mm.

### Electrical Characteristics

$T_A = 25^\circ\text{C}$  unless otherwise noted

| Symbol | Parameter                                                                                                                                                                    | Value | Units         |
|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|---------------|
| $V_F$  | Forward Voltage @ $I_F = 500\text{ mA}$ ,<br>$I_F = 500\text{ mA}$ , $T_A = 100^\circ\text{C}$<br>$I_F = 1.0\text{ A}$ ,<br>$I_F = 1.0\text{ A}$ , $T_A = 100^\circ\text{C}$ | 510   | mV            |
|        |                                                                                                                                                                              | 460   | mV            |
|        |                                                                                                                                                                              | 620   | mV            |
|        |                                                                                                                                                                              | 610   | mV            |
| $I_R$  | Reverse Current @ $V_R = 20\text{ V}$ ,<br>$V_R = 20\text{ V}$ , $T_A = 100^\circ\text{C}$<br>$V_R = 40\text{ V}$ ,<br>$V_R = 40\text{ V}$ , $T_A = 100^\circ\text{C}$       | 10    | $\mu\text{A}$ |
|        |                                                                                                                                                                              | 5.0   | mA            |
|        |                                                                                                                                                                              | 20    | $\mu\text{A}$ |
|        |                                                                                                                                                                              | 13    | mA            |

Typical Characteristics




Figure 1. Forward Voltage Characteristics




Figure 2. Reverse Current vs Reverse Voltage




Figure 3. Total Capacitance

## TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

|                      |                     |                              |                       |      |
|----------------------|---------------------|------------------------------|-----------------------|------|
| ACE <sup>Ex</sup> ™  | FAST <sup>®</sup>   | OPTOLOGIC™                   | SMART START™          | VCX™ |
| Bottomless™          | FAST <sup>r</sup> ™ | OPTOPLANAR™                  | STAR*POWER™           |      |
| CoolFET™             | FRFET™              | PACMAN™                      | Stealth™              |      |
| CROSSVOLT™           | GlobalOptoisolator™ | POP™                         | SuperSOT™-3           |      |
| DenseTrench™         | GTO™                | Power247™                    | SuperSOT™-6           |      |
| DOME™                | HiSeC™              | PowerTrench <sup>®</sup>     | SuperSOT™-8           |      |
| EcoSPARK™            | ISOPLANAR™          | QFET™                        | SyncFET™              |      |
| E <sup>2</sup> CMOS™ | LittleFET™          | QS™                          | TinyLogic™            |      |
| EnSigna™             | MicroFET™           | QT Optoelectronics™          | TruTranslation™       |      |
| FACT™                | MicroPak™           | Quiet Series™                | UHC™                  |      |
| FACT Quiet Series™   | MICROWIRE™          | SILENT SWITCHER <sup>®</sup> | UltraFET <sup>®</sup> |      |

STAR\*POWER is used under license

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## PRODUCT STATUS DEFINITIONS

### Definition of Terms

| Datasheet Identification | Product Status         | Definition                                                                                                                                                                                                            |
|--------------------------|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Advance Information      | Formative or In Design | This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.                                                                                    |
| Preliminary              | First Production       | This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design. |
| No Identification Needed | Full Production        | This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.                                                       |
| Obsolete                 | Not In Production      | This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.                                                   |