


Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Test disconnect terminal block, nom. voltage: 1000 V, nominal current: 30 A, connection method: Push-in connection, Rated cross section: 6 mm², cross section: 0.5 mm² - 6 mm², color: red

Your advantages

- Increased safety with 1,000 V nominal voltage
- The compact design allows an overall width the same as screw terminal blocks
- Quick and easy actuation with the screw-free disconnect slide
- Clearly visible and readily apparent switching state
- Use of CLIPLINE complete standard accessories

Commercial Data

Item number	1350427
Packing unit	1 pc
Minimum order quantity	50 pc
Sales Key	B02
Product Key	BE2333
GTIN	4063151670313
Weight per Piece (including packing)	21.54 g
Weight per Piece (excluding packing)	21.54 g
Customs tariff number	85369010
Country of origin	CN

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Technical Data

Product properties

Product type	Test disconnect terminal block
Number of connections	2
Number of rows	1
Potentials	1

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	8 kV
Maximum power dissipation for nominal condition	1.31 W

Connection data

Number of connections per level	2
Nominal cross section	6 mm ²

Level 1+2

Stripping length	10 mm ... 12 mm
Internal cylindrical gage	A4
	B4
Conductor cross section solid	0.5 mm ² ... 6 mm ²
Cross section AWG	20 ... 10
Conductor cross section flexible	0.5 mm ² ... 6 mm ²
Conductor cross section, flexible [AWG]	20 ... 10
Flexible conductor cross section flexible (ferrule, w/o plastic sleeve)	0.5 mm ² ... 6 mm ² Connection only with corresponding crimp versions.
Flexible conductor cross section (ferrule with plastic sleeve)	0.5 mm ² ... 6 mm ² Connection only with corresponding crimp versions.
Conductor cross-section flexible (2 conductors with the same cross-section, with TWIN ferrule and plastic sleeve)	0.5 mm ² ... 2.5 mm ²
Nominal current	30 A (with 6 mm ² conductor cross section)
Maximum load current	30 A (with 6 mm ² conductor cross section)
Nominal voltage	1000 V
Nominal cross section	6 mm ²

Level 1+2 Connection cross sections directly pluggable

Conductor cross section solid	0.75 mm ² ... 6 mm ²
Flexible conductor cross section flexible (ferrule, w/o plastic sleeve)	1.5 mm ² ... 6 mm ² Connection only with corresponding crimp versions.
Flexible conductor cross section (ferrule with plastic sleeve)	1 mm ² ... 6 mm ² Connection only with corresponding crimp versions.

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Dimensions

Width	8.2 mm
End cover width	2.2 mm
Height NS 35/15	62 mm
Height NS 35/7,5	54.5 mm
Length	82 mm

Material specifications

Color	red
Flammability rating according to UL 94	V0
Insulating material group	I
Insulating material	PA
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	125 °C
Relative insulation material temperature index (Elec., UL 746 B)	125 °C

Electrical tests

Surge voltage test

Test voltage setpoint	9.8 kV
Result	Test passed

Temperature-rise test

Requirement temperature-rise test	Increase in temperature ≤ 45 K
Result	Test passed
Short-time withstand current 4 mm ²	0.5 kA
	0.15 kA
	1.25 kA
Result	Test passed

Power-frequency withstand voltage

Test voltage setpoint	2.2 kV
Result	Test passed

Mechanical properties

Mechanical data

Open side panel	Yes
-----------------	-----

Mechanical tests

Mechanical strength

Result	Test passed
--------	-------------

Test for conductor damage and slackening

Rotation speed	10 rpm
----------------	--------

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Revolutions	135
Conductor cross section/weight	0.5 mm ² / 0.3 kg
	6 mm ² / 1.4 kg
Result	Test passed

Environmental and real-life conditions

Aging

Result	Test passed
--------	-------------

Needle-flame test

Time of exposure	30 s
Result	Test passed

Oscillation/broadband noise

Specification	DIN EN 50155 (VDE 0115-200):2018-05
Spectrum	Service life test category 2, bogie-mounted
Frequency	$f_1 = 5 \text{ Hz}$ to $f_2 = 250 \text{ Hz}$
ASD level	6.12 (m/s ²) ² /Hz
Acceleration	3.12g
Test duration per axis	5 h
Test directions	X-, Y- and Z-axis
Result	Test passed

Shocks

Pulse shape	Half-sine
Acceleration	30g
Shock duration	18 ms
Number of shocks per direction	3
Test directions	X-, Y- and Z-axis (pos. and neg.)
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

Standards and regulations

Connection in acc. with standard	IEC 60947-7-1
----------------------------------	---------------

Mounting

Mounting type	NS 35/15
	NS 35/7,5

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Approvals

 CSA Approval ID: 158887				
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
Use group B				
	600 V	30 A	26 - 10	-
Use group C				
	600 V	30 A	26 - 10	-

 cULus Recognized Approval ID: E60425				
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
Use group B				
	600 V	30 A	26 - 10	-
Use group C				
	600 V	30 A	26 - 10	-
Use group F				
	1000 V	30 A	26 - 10	-

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Classifications

ECLASS

ECLASS-11.0	27141126
-------------	----------

ETIM

ETIM 8.0	EC000902
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Accessories



Note: Applying some accessories below might limit this product.

Plug-in bridge

Plug-in bridge - FBS 2-8 - 3030284

<https://www.phoenixcontact.com/us/products/3030284>



Plug-in bridge, pitch: 8.2 mm, color: red



Max. current carrying capacity: 30 A

Plug-in bridge

Plug-in bridge - FBS 3-8 - 3030297

<https://www.phoenixcontact.com/us/products/3030297>



Plug-in bridge, pitch: 8.2 mm, color: red



Max. current carrying capacity: 30 A

Test disconnect terminal block - PTVME 6/S RD

1350427

<https://www.phoenixcontact.com/us/products/1350427>

Plug-in bridge

Plug-in bridge - FBS 4-8 - 3030307

<https://www.phoenixcontact.com/us/products/3030307>



Plug-in bridge, pitch: 8.2 mm, color: red

 Max. current carrying capacity: 30 A

Plug-in bridge

Plug-in bridge - FBS 5-8 - 3030310

<https://www.phoenixcontact.com/us/products/3030310>



Plug-in bridge, pitch: 8.2 mm, color: red

 Max. current carrying capacity: 30 A

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Plug-in bridge

Plug-in bridge - FBS 6-8 - 3032470

<https://www.phoenixcontact.com/us/products/3032470>

Plug-in bridge, pitch: 8.2 mm, color: red



 Max. current carrying capacity: 30 A

Plug-in bridge

Plug-in bridge - FBS 10-8 - 3030323

<https://www.phoenixcontact.com/us/products/3030323>

Plug-in bridge, pitch: 8.2 mm, color: red



 Max. current carrying capacity: 30 A

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Plug-in bridge

Plug-in bridge - FBS 1/3-8 - 3032363

<https://www.phoenixcontact.com/us/products/3032363>



Plug-in bridge, pitch: 8.2 mm, pin assignment: 1,3, color: red

 Max. current carrying capacity: 30 A

Plug-in bridge

Plug-in bridge - FBS 1/4-8 - 3032376

<https://www.phoenixcontact.com/us/products/3032376>



Plug-in bridge, pitch: 8.2 mm, pin assignment: 1, 4, color: red

 Max. current carrying capacity: 30 A

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Plug-in bridge

Plug-in bridge - FBS 1/5-8 - 3032381

<https://www.phoenixcontact.com/us/products/3032381>



Plug-in bridge, pitch: 8.2 mm, pin assignment: 1,5, color: red

 Max. current carrying capacity: 30 A

Plug-in bridge

Plug-in bridge - FBS 1/3/5-8 - 3032389

<https://www.phoenixcontact.com/us/products/3032389>



Plug-in bridge, pitch: 8.2 mm, pin assignment: 1,3,5, color: red

 Max. current carrying capacity: 30 A

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Plug-in bridge

Plug-in bridge - FBS 1/4/7/10-8 - 3032402

<https://www.phoenixcontact.com/us/products/3032402>

Plug-in bridge, pitch: 8.2 mm, pin assignment: 1,4,7,10, color: red



 Max. current carrying capacity: 30 A

Plug-in bridge

Plug-in bridge - FBS 1/3/5/7-8 - 3030396

<https://www.phoenixcontact.com/us/products/3030396>

Plug-in bridge, Version with single- or double-sided cutting edge. Please keep in mind the possible impact on touch protection as well as air clearances and creepage distances., pitch: 8.2 mm, pin assignment: 1, 3, 5, 7, color: red



 Max. current carrying capacity: 30 A

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Plug-in bridge

Plug-in bridge - FBS 1/2/4-8 - 3032377

<https://www.phoenixcontact.com/us/products/3032377>



Plug-in bridge, pitch: 8.2 mm, pin assignment: 1,2,4, color: red

 Max. current carrying capacity: 30 A

Short-circuit connector

Short-circuit connector - FBSRH 2-8 - 3033802

<https://www.phoenixcontact.com/us/products/3033802>



Short-circuit connector, pitch: 8.2 mm, color: red

 Max. current carrying capacity: 32 A

Test disconnect terminal block - PTVME 6/S RD

1350427

<https://www.phoenixcontact.com/us/products/1350427>

Short-circuit connector

Short-circuit connector - FBSRH 3-8 - 3033803

<https://www.phoenixcontact.com/us/products/3033803>



Short-circuit connector, pitch: 8.2 mm, color: red

 Max. current carrying capacity: 32 A

Short-circuit connector

Short-circuit connector - FBSRH 4-8 - 3033804

<https://www.phoenixcontact.com/us/products/3033804>



Short-circuit connector, pitch: 8.2 mm, color: red

 Max. current carrying capacity: 32 A

Test disconnect terminal block - PTVME 6/S RD

1350427

<https://www.phoenixcontact.com/us/products/1350427>

Plug-in bridge

Plug-in bridge - FBSR 2-8 - 3033808

<https://www.phoenixcontact.com/us/products/3033808>



Plug-in bridge, pitch: 8.2 mm, color: red

 Max. current carrying capacity: 30 A

Plug-in bridge

Plug-in bridge - FBSR 3-8 - 3001597

<https://www.phoenixcontact.com/us/products/3001597>



Plug-in bridge, pitch: 8.2 mm, color: red

 Max. current carrying capacity: 30 A

Test disconnect terminal block - PTVME 6/S RD

1350427

<https://www.phoenixcontact.com/us/products/1350427>

Plug-in bridge

Plug-in bridge - FBSR 4-8 - 3000585

<https://www.phoenixcontact.com/us/products/3000585>



Plug-in bridge, pitch: 8.2 mm, color: red

 Max. current carrying capacity: 30 A

Plug-in bridge

Plug-in bridge - FBSR 5-8 - 3033809

<https://www.phoenixcontact.com/us/products/3033809>



Plug-in bridge, pitch: 8.2 mm, color: red

 Max. current carrying capacity: 30 A

Test disconnect terminal block - PTVME 6/S RD

1350427

<https://www.phoenixcontact.com/us/products/1350427>

Plug-in bridge

Plug-in bridge - FBSR 10-8 - 3001599

<https://www.phoenixcontact.com/us/products/3001599>

Plug-in bridge, pitch: 8.2 mm, color: red



 Max. current carrying capacity: 30 A

Plug-in bridge

Plug-in bridge - FBSR 16-8 - 3033816

<https://www.phoenixcontact.com/us/products/3033816>

Plug-in bridge, pitch: 8.2 mm, color: red



 Max. current carrying capacity: 30 A

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Plug-in bridge

Plug-in bridge - FBSR 1/6/11/14-8 - 3033822

<https://www.phoenixcontact.com/us/products/3033822>



Plug-in bridge, non-adjacent, pitch: 8.2 mm, pin assignment: 1, 6, 11, 14, color: red

 Max. current carrying capacity: 30 A

Plug-in bridge

Plug-in bridge - FBSR 1/6/11/16-8 - 3033820

<https://www.phoenixcontact.com/us/products/3033820>



Plug-in bridge, non-adjacent, pitch: 8.2 mm, pin assignment: 1, 6, 11, 16, color: red

 Max. current carrying capacity: 30 A

Test disconnect terminal block - PTVME 6/S RD




1350427

<https://www.phoenixcontact.com/us/products/1350427>

Plug-in bridge

Plug-in bridge - FBSR 1/7/13/16-8 - 3033821

<https://www.phoenixcontact.com/us/products/3033821>



Plug-in bridge, non-adjacent, pitch: 8.2 mm, pin assignment: 1, 7, 13, 16, color: red

 Max. current carrying capacity: 30 A

Switching jumper

Switching jumper - SB-MER 2-8 - 3000587

<https://www.phoenixcontact.com/us/products/3000587>



Switching jumper, pitch: 8.2 mm, color: gray/orange

 Max. current carrying capacity: 25 A

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Switching jumper

Switching jumper - SB-MER 3-8 - 3000588

<https://www.phoenixcontact.com/us/products/3000588>



Switching jumper, pitch: 8.2 mm, color: gray/orange

 Max. current carrying capacity: 25 A

Switching jumper

Switching jumper - SB-MER 4-8 - 3000589

<https://www.phoenixcontact.com/us/products/3000589>



Switching jumper, pitch: 8.2 mm, color: gray/orange

 Max. current carrying capacity: 25 A

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Plug-in bridge

Plug-in bridge - FBS 2-8 CT - 3033830

<https://www.phoenixcontact.com/us/products/3033830>



Plug-in bridge, pitch: 8.2 mm, color: orange

 Max. current carrying capacity: 30 A

Plug-in bridge

Plug-in bridge - FBS 3-8 CT - 3033831

<https://www.phoenixcontact.com/us/products/3033831>



Plug-in bridge, pitch: 8.2 mm, color: orange

 Max. current carrying capacity: 30 A

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Plug-in bridge

Plug-in bridge - FBS 4-8 CT - 3033832

<https://www.phoenixcontact.com/us/products/3033832>



Plug-in bridge, pitch: 8.2 mm, color: orange

 Max. current carrying capacity: 30 A

Plug-in bridge

Plug-in bridge - FBS 10-8 CT - 3033833

<https://www.phoenixcontact.com/us/products/3033833>



Plug-in bridge, pitch: 8.2 mm, color: orange

 Max. current carrying capacity: 30 A

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Plug-in bridge

Plug-in bridge - FBS 2-8 BU - 3032567

<https://www.phoenixcontact.com/us/products/3032567>



Plug-in bridge, pitch: 8.2 mm, color: blue

 Max. current carrying capacity: 30 A

Plug-in bridge

Plug-in bridge - FBS 3-8 BU - 3032570

<https://www.phoenixcontact.com/us/products/3032570>



Plug-in bridge, pitch: 8.2 mm, color: blue

 Max. current carrying capacity: 30 A

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Plug-in bridge

Plug-in bridge - FBS 4-8 BU - 3032583

<https://www.phoenixcontact.com/us/products/3032583>



Plug-in bridge, pitch: 8.2 mm, color: blue

 Max. current carrying capacity: 30 A

Plug-in bridge

Plug-in bridge - FBS 5-8 BU - 3032596

<https://www.phoenixcontact.com/us/products/3032596>



Plug-in bridge, pitch: 8.2 mm, color: blue

 Max. current carrying capacity: 30 A

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Plug-in bridge

Plug-in bridge - FBS 6-8 BU - 3032677

<https://www.phoenixcontact.com/us/products/3032677>



Plug-in bridge, pitch: 8.2 mm, color: blue

 Max. current carrying capacity: 30 A

Plug-in bridge

Plug-in bridge - FBS 10-8 BU - 3032606

<https://www.phoenixcontact.com/us/products/3032606>



Plug-in bridge, pitch: 8.2 mm, color: blue

 Max. current carrying capacity: 30 A

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

End cover

End cover - D-PTVME 6/S - 1164789

<https://www.phoenixcontact.com/us/products/1164789>

End cover, length: 82 mm, width: 0.8 mm, height: 46.5 mm, color: gray



Test plugs

Test plugs - MPS-MT/ 4MM - 3048577

<https://www.phoenixcontact.com/us/products/3048577>

Test plugs, with solder connection up to 1 mm² conductor cross section, color: silver



Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Separating plate

Separating plate - TS-PTVME 6/S - 1193381

<https://www.phoenixcontact.com/us/products/1193381>

Separating plate, length: 82 mm, width: 0.8 mm, height: 51.5 mm, color: gray



Insulating sleeve

Insulating sleeve - MPS-IH WH - 0201663

<https://www.phoenixcontact.com/us/products/0201663>

Insulating sleeve, color: white



Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Short-circuit connector

Short-circuit connector - KSS 8 - 0311540

<https://www.phoenixcontact.com/us/products/0311540>



Short-circuit connector, pitch: 8 mm, color: black

Insulating sleeve

Insulating sleeve - MPS-IH RD - 0201676

<https://www.phoenixcontact.com/us/products/0201676>



Insulating sleeve, color: red

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Short-circuit connector

Short-circuit connector - KSS 4- 8 - 0309549

<https://www.phoenixcontact.com/us/products/0309549>




Short-circuit connector, pitch: 8 mm, color: black

Insulating sleeve

Insulating sleeve - MPS-IH BU - 0201689

<https://www.phoenixcontact.com/us/products/0201689>



Insulating sleeve, color: blue

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Female test connector

Female test connector - TPS 3/20/5 - 3246586

<https://www.phoenixcontact.com/us/products/3246586>



Female test connector, for 4 mm test plugs, for screwing into the bridge shaft,
color: silver

Insulating sleeve

Insulating sleeve - MPS-IH YE - 0201692

<https://www.phoenixcontact.com/us/products/0201692>



Insulating sleeve, color: yellow

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Screwdriver

Screwdriver - SZS 1,0X4,0 VDE - 1205066

<https://www.phoenixcontact.com/us/products/1205066>



Screwdriver, slot-headed, VDE insulated, size: 1.0 x 4.0 x 100 mm, 2-component grip, with non-slip grip

Insulating sleeve

Insulating sleeve - MPS-IH GN - 0201702

<https://www.phoenixcontact.com/us/products/0201702>

Insulating sleeve, color: green



Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Screwdriver

Screwdriver - SF-SL 0,8X4,0-100 S-VDE - 1212588

<https://www.phoenixcontact.com/us/products/1212588>



Actuation tool, for ST terminal blocks, VDE insulated, with slimmer insulation integrated in the blade, also suitable for use as a bladed screwdriver, size: 0.8 x 4.0 x 100 mm, 2-component grip, with non-slip grip

Insulating sleeve

Insulating sleeve - MPS-IH GY - 0201728

<https://www.phoenixcontact.com/us/products/0201728>

Insulating sleeve, color: gray



Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Cover profile

Cover profile - AP-ME METER - 3034361

<https://www.phoenixcontact.com/us/products/3034361>



Cover profile, for covering terminal strips, snapped onto APT-ME cover profile carrier or APH-ME end bracket. A cover profile carrier should be positioned at the ends and at intervals of around 40 cm. Length supplied: 1 m

Insulating sleeve

Insulating sleeve - MPS-IH BK - 0201731

<https://www.phoenixcontact.com/us/products/0201731>

Insulating sleeve, color: black



Test disconnect terminal block - PTVME 6/S RD



1350427


<https://www.phoenixcontact.com/us/products/1350427>

Cover profile carrier

Cover profile carrier - APH-ME - 3034374

<https://www.phoenixcontact.com/us/products/3034374>

Cover profile carrier, for mounting on NS 35/7,5 DIN rail, for fixing the AP-ME cover profile, can be sealed as an option



Test plugs

Test plugs - PS-8 - 3031005

<https://www.phoenixcontact.com/us/products/3031005>

Test plugs, Modular test plug, color: red



Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Cover profile carrier

Cover profile carrier - APT-ME - 3034358

<https://www.phoenixcontact.com/us/products/3034358>

Cover profile carrier for mounting on NS 35/7.5 DIN rail for attaching the cover profile AP-ME



Spacer plate

Spacer plate - DP PS-8 - 3036741

<https://www.phoenixcontact.com/us/products/3036741>

Spacer plate, length: 22.4 mm, width: 8.2 mm, height: 29 mm, number of positions: 1, color: red



Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Covering hood

Covering hood - AH-ME - 3240265

<https://www.phoenixcontact.com/us/products/3240265>



Cover, for the contact- and dust-protected encapsulation of the components

Test plugs

Test plugs - PS-8/2,3MM RD - 3048564

<https://www.phoenixcontact.com/us/products/3048564>



Test plugs, color: red

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Switching lock

Switching lock - SL-SB - 3035761

<https://www.phoenixcontact.com/us/products/3035761>



Switching lock, for additional locking of short-circuit switching elements in current transformer measuring circuits, length: 16.3 mm, width: 12.5 mm, height: 13.6 mm, color: white

Test adapter

Test adapter - PAI-4-FIX BU - 3032729

<https://www.phoenixcontact.com/us/products/3032729>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, color: blue

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Screw bridge

Screw bridge - SCBI 10-8,15 - 3245134

<https://www.phoenixcontact.com/us/products/3245134>

Screw bridge, with insulating collar, pitch: 8.2 mm, color: silver



Test adapter

Test adapter - PAI-4-FIX OG - 3034455

<https://www.phoenixcontact.com/us/products/3034455>

4 mm test adapter, for terminal blocks with 8.2 mm pitch



Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Isolator bridge bar

Isolator bridge bar - SCBI 10-8,15 ISO - 3000417

<https://www.phoenixcontact.com/us/products/3000417>



Isolator bridge bar, for switchable cross bridges, with insulating collar, pitch: 8.2 mm, color: silver

Test adapter

Test adapter - PAI-4-FIX YE - 3032745

<https://www.phoenixcontact.com/us/products/3032745>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, color: yellow

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Crimping pliers

Crimping pliers - CRIMPFOX 6 - 1212034

<https://www.phoenixcontact.com/us/products/1212034>



Crimping pliers, for ferrules without insulating collar according to DIN 46228 Part 1 and ferrules with insulating collar according to DIN 46228 Part 4, 0.25 mm² ... 6.0 mm², lateral entry, trapezoidal crimp

Test adapter

Test adapter - PAI-4-FIX RD - 3032732

<https://www.phoenixcontact.com/us/products/3032732>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, color: red

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Crimping pliers

Crimping pliers - CRIMPFOX 6S-F - 1212043

<https://www.phoenixcontact.com/us/products/1212043>



Crimping pliers, for ferrules without insulating collar according to DIN 46228 Part 1 and ferrules with insulating collar according to DIN 46228 Part 4, 0.5 mm² ... 6 mm², front entry, square crimp

Test adapter

Test adapter - PAI-4-FIX GN - 3032758

<https://www.phoenixcontact.com/us/products/3032758>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, color: green

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Crimping pliers

Crimping pliers - CRIMPFOX 10S - 1212045

<https://www.phoenixcontact.com/us/products/1212045>



Crimping pliers, for ferrules without insulating collar according to DIN 46228 Part 1 and ferrules with insulating collar according to DIN 46228 Part 4, 0.14 mm² ... 10 mm², unlockable pressure lock, lateral entry

Test adapter

Test adapter - PAI-4-FIX BK - 3032774

<https://www.phoenixcontact.com/us/products/3032774>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, color: black

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Crimping pliers

Crimping pliers - CRIMPFOX 10T-F - 1134913

<https://www.phoenixcontact.com/us/products/1134913>



Crimping pliers, type of contact: Insulated and uninsulated ferrules, standards/specifications: DIN 46228-1, DIN 46228-4, min. cross section: 0.14 mm², max. cross section: 10 mm², For TWIN ferrules up to 2 x 4 mm², automatic cross section adjustment, frontal insertion, compression: Trapezoidal crimp, black

Test adapter

Test adapter - PAI-4-FIX GY - 3032790

<https://www.phoenixcontact.com/us/products/3032790>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, color: gray

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Crimping pliers

Crimping pliers - CRIMPFOX 6-M - 1212720

<https://www.phoenixcontact.com/us/products/1212720>



Crimping pliers, for ferrules without insulating collar according to DIN 46228 Part 1 and ferrules with insulating collar according to DIN 46228 Part 4, 0.25 mm² ... 6.0 mm², lateral entry, trapezoidal crimp

Test adapter

Test adapter - PAI-4-FIX VT - 3032761

<https://www.phoenixcontact.com/us/products/3032761>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 4.2 mm . . 8.2 mm pitch, color: violet

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Crimping pliers

Crimping pliers - CRIMPFOX 10 - 1212721

<https://www.phoenixcontact.com/us/products/1212721>



Crimping pliers, for ferrules without insulating collar according to DIN 46228 Part 1 and ferrules with insulating collar according to DIN 46228 Part 4, 4 mm² ... 10 mm², lateral entry, trapezoidal crimp

Test adapter

Test adapter - PAI-4-FIX BN - 3032787

<https://www.phoenixcontact.com/us/products/3032787>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, color: brown

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Crimping pliers

Crimping pliers - CRIMPFOX DUO 10 - 1031721

<https://www.phoenixcontact.com/us/products/1031721>



Crimping pliers, type of contact: Insulated and uninsulated ferrules, min. cross section: 0.14 mm², max. cross section: 10 mm², for TWIN ferrules up to 2 x 4 mm², automatic cross section adjustment, rotating die, lateral and frontal insertion, compression: Trapezoidal crimp, black/green

Test adapter

Test adapter - PAI-4-FIX WH - 3032797

<https://www.phoenixcontact.com/us/products/3032797>



4 mm test adapter, for terminal blocks with 8.2 mm pitch

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Short-circuit connector

Short-circuit connector - KSSI 2-8 - 3000722

<https://www.phoenixcontact.com/us/products/3000722>



Short-circuit connector, pitch: 8 mm, color: black

Test adapter

Test adapter - PAIS-4-FIX GY - 3032791

<https://www.phoenixcontact.com/us/products/3032791>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, color: gray

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Short-circuit connector

Short-circuit connector - KSSI 4-8 - 3000735

<https://www.phoenixcontact.com/us/products/3000735>



Short-circuit connector, pitch: 8 mm, color: black

Test adapter

Test adapter - PAIS-4-FIX BK - 3032792

<https://www.phoenixcontact.com/us/products/3032792>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, color: black

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Operating lever

Operating lever - C-ME 6/1 - 3034441

<https://www.phoenixcontact.com/us/products/3034441>



Operating lever, for switching test disconnect terminal blocks on and off

Test adapter

Test adapter - PAIS-4-FIX RD - 3032793

<https://www.phoenixcontact.com/us/products/3032793>



Test adapter, Do not plug in while the power is connected, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, color: red

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Operating lever

Operating lever - C-ME 6/2 - 3034442

<https://www.phoenixcontact.com/us/products/3034442>



Operating lever, length: 5 mm, width: 16 mm, height: 5 mm, number of positions: 2, color: orange

Test adapter

Test adapter - PAIS-4-FIX BU - 3032798

<https://www.phoenixcontact.com/us/products/3032798>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, color: blue

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Operating lever

Operating lever - C-ME 6/3 - 3034390

<https://www.phoenixcontact.com/us/products/3034390>

Operating lever, length: 5 mm, width: 24.1 mm, height: 5 mm, number of positions: 3, color: orange



Test adapter

Test adapter - PAIS-4-FIX YE - 3032799

<https://www.phoenixcontact.com/us/products/3032799>

Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, color: yellow



Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Switching lock

Switching lock - S-ME 6 - 3034439

<https://www.phoenixcontact.com/us/products/3034439>

Switching lock, length: 12 mm, width: 8.2 mm, color: white



Test adapter

Test adapter - PAIS-4-FIX GN - 3032801

<https://www.phoenixcontact.com/us/products/3032801>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, color: green

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Test adapter

Test adapter - PAIS-4-FIX VT - 3032802

<https://www.phoenixcontact.com/us/products/3032802>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, color: violet

Female test connector

Female test connector - PSBJ 6-T GY - 3070316

<https://www.phoenixcontact.com/us/products/3070316>



Female test connector, color: gray

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Female test connector

Female test connector - PSBJ 6-T BN - 3070317

<https://www.phoenixcontact.com/us/products/3070317>



Female test connector, color: brown

Female test connector

Female test connector - PSBJ 6-T BK - 3070318

<https://www.phoenixcontact.com/us/products/3070318>



Female test connector, color: black

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Female test connector

Female test connector - PSBJ 6-T RD - 3070319

<https://www.phoenixcontact.com/us/products/3070319>



Female test connector, color: red

Female test connector

Female test connector - PSBJ 6-T OG - 3070320

<https://www.phoenixcontact.com/us/products/3070320>



Female test connector, color: orange

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Female test connector

Female test connector - PSBJ 6-T WH - 3070324

<https://www.phoenixcontact.com/us/products/3070324>

Female test connector, color: white



Female test connector

Female test connector - PSBJ 6-T YE - 3070326

<https://www.phoenixcontact.com/us/products/3070326>

Female test connector, color: yellow



Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Female test connector

Female test connector - PSBJ 6-T GN - 3070327

<https://www.phoenixcontact.com/us/products/3070327>



Female test connector, color: green

Female test connector

Female test connector - PSBJ 6-T VT - 3070328

<https://www.phoenixcontact.com/us/products/3070328>



Female test connector, color: violet

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Female test connector

Female test connector - PSBJ 6-T BU - 3070329

<https://www.phoenixcontact.com/us/products/3070329>


Female test connector, color: blue



Zack marker strip

Zack marker strip - ZB 8:UNBEDRUCKT - 1052002

<https://www.phoenixcontact.com/us/products/1052002>



Zack marker strip, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, PLOTMARK, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

Test disconnect terminal block - PTVME 6/S RD




1350427

<https://www.phoenixcontact.com/us/products/1350427>

Zack marker strip

Zack marker strip - ZB 8 CUS - 0825011

<https://www.phoenixcontact.com/us/products/0825011>



Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

Marker for terminal blocks

Marker for terminal blocks - UC-TM 8 - 0818072

<https://www.phoenixcontact.com/us/products/0818072>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 56

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Marker for terminal blocks

Marker for terminal blocks - UC-TM 8 CUS - 0824597

<https://www.phoenixcontact.com/us/products/0824597>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 56

Marker for terminal blocks

Marker for terminal blocks - UCT-TM 8 - 0828740

<https://www.phoenixcontact.com/us/products/0828740>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 42

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Marker for terminal blocks

Marker for terminal blocks - UCT-TM 8 CUS - 0829616

<https://www.phoenixcontact.com/us/products/0829616>




Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 42

Zack marker strip

Zack marker strip - ZB 8,LGS:FORTL.ZAHLEN - 1052015

<https://www.phoenixcontact.com/us/products/1052015>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

Test disconnect terminal block - PTVME 6/S RD




1350427

<https://www.phoenixcontact.com/us/products/1350427>

Zack marker strip

Zack marker strip - ZB 8,QR:FORTL.ZAHLEN - 1052028

<https://www.phoenixcontact.com/us/products/1052028>




Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

Marker for terminal blocks

Marker for terminal blocks - ZB 8,LGS:L1-N,PE - 1052413

<https://www.phoenixcontact.com/us/products/1052413>



Marker for terminal blocks, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, horizontal: L1, L2, L3, N, PE, L1, L2, L3, N, PE, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

DIN rail perforated

DIN rail perforated - NS 35/ 7,5 PERF 2000MM - 0801733

<https://www.phoenixcontact.com/us/products/0801733>



DIN rail perforated, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver, Pack of 25 (50 m)

DIN rail, unperforated

DIN rail, unperforated - NS 35/ 7,5 UNPERF 2000MM - 0801681

<https://www.phoenixcontact.com/us/products/0801681>



DIN rail, unperforated, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver, Pack of 25 (50 m)

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

DIN rail perforated

DIN rail perforated - NS 35/ 7,5 WH PERF 2000MM - 1204119

<https://www.phoenixcontact.com/us/products/1204119>



DIN rail perforated, acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver, Pack of 25 (50 m)

DIN rail, unperforated

DIN rail, unperforated - NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - 1204122

<https://www.phoenixcontact.com/us/products/1204122>



DIN rail, unperforated, acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver, Pack of 10 (20 m)

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

DIN rail, unperforated

DIN rail, unperforated - NS 35/ 7,5 AL UNPERF 2000MM - 0801704

<https://www.phoenixcontact.com/us/products/0801704>



DIN rail, unperforated, acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver, Pack of 25 (50 m)

DIN rail perforated

DIN rail perforated - NS 35/ 7,5 ZN PERF 2000MM - 1206421

<https://www.phoenixcontact.com/us/products/1206421>



DIN rail perforated, acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver, Pack of 25 (50 m)

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

DIN rail, unperforated

DIN rail, unperforated - NS 35/ 7,5 ZN UNPERF 2000MM - 1206434

<https://www.phoenixcontact.com/us/products/1206434>



DIN rail, unperforated, acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver, Pack of 25 (50 m)

DIN rail, unperforated

DIN rail, unperforated - NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - 0801762

<https://www.phoenixcontact.com/us/products/0801762>



DIN rail, unperforated, acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored, Pack of 10 (20 m)

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

End cap

End cap - NS 35/ 7,5 CAP - 1206560

<https://www.phoenixcontact.com/us/products/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



DIN rail perforated

DIN rail perforated - NS 35/15 PERF 2000MM - 1201730

<https://www.phoenixcontact.com/us/products/1201730>



DIN rail perforated, similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver, Pack of 25 (50 m)

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

DIN rail, unperforated

DIN rail, unperforated - NS 35/15 UNPERF 2000MM - 1201714

<https://www.phoenixcontact.com/us/products/1201714>



DIN rail, unperforated, similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver, Pack of 25 (50 m)

DIN rail perforated

DIN rail perforated - NS 35/15 WH PERF 2000MM - 0806602

<https://www.phoenixcontact.com/us/products/0806602>



DIN rail perforated, similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: white, Pack of 25 (50 m)

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

DIN rail, unperforated

DIN rail, unperforated - NS 35/15 WH UNPERF 2000MM-VPE 10 - 1204135

<https://www.phoenixcontact.com/us/products/1204135>



DIN rail, unperforated, similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver, Pack of 10 (20 m)

DIN rail, unperforated

DIN rail, unperforated - NS 35/15 AL UNPERF 2000MM - 1201756

<https://www.phoenixcontact.com/us/products/1201756>



DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

DIN rail perforated

DIN rail perforated - NS 35/15 ZN PERF 2000MM - 1206599

<https://www.phoenixcontact.com/us/products/1206599>



DIN rail perforated, similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver, Pack of 25 (50 m)

DIN rail, unperforated

DIN rail, unperforated - NS 35/15 ZN UNPERF 2000MM - 1206586

<https://www.phoenixcontact.com/us/products/1206586>



DIN rail, unperforated, similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver, Pack of 25 (50 m)

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

DIN rail, unperforated

DIN rail, unperforated - NS 35/15 CU UNPERF 2000MM-VPE 10 - 1201895

<https://www.phoenixcontact.com/us/products/1201895>



DIN rail, unperforated, similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored, Pack of 10 (20 m)

End cap

End cap - NS 35/15 CAP - 1206573

<https://www.phoenixcontact.com/us/products/1206573>

DIN rail end piece, for DIN rail NS 35/15



Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

End clamp

End clamp - CLIPFIX 35 - 3022218

<https://www.phoenixcontact.com/us/products/3022218>

Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, width: 9.5 mm, color: gray



End clamp

End clamp - CLIPFIX 35-5 - 3022276

<https://www.phoenixcontact.com/us/products/3022276>

Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, with parking option for FBS...5, FBS...6, KSS 5, KSS 6, width: 5.15 mm, color: gray



Test disconnect terminal block - PTVME 6/S RD



1350427


<https://www.phoenixcontact.com/us/products/1350427>

End clamp

End clamp - E/NS 35 N - 0800886

<https://www.phoenixcontact.com/us/products/0800886>

End clamp, width: 9.5 mm, color: gray



Zack Marker strip, flat

Zack Marker strip, flat - ZBF 8:UNBEDRUCKT - 0808781

<https://www.phoenixcontact.com/us/products/0808781>



Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 8 mm, lettering field size: 5.15 x 8.15 mm, Number of individual labels: 10

Test disconnect terminal block - PTVME 6/S RD

1350427

<https://www.phoenixcontact.com/us/products/1350427>

Zack Marker strip, flat

Zack Marker strip, flat - ZBF 8 CUS - 0825030

<https://www.phoenixcontact.com/us/products/0825030>



Zack Marker strip, flat, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 8 mm, lettering field size: 5.15 x 8.15 mm, Number of individual labels: 10

Zack Marker strip, flat

Zack Marker strip, flat - ZBF 8,LGS:FORTL.ZAHLEN - 0808804

<https://www.phoenixcontact.com/us/products/0808804>



Zack Marker strip, flat, Strip, white, labeled, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 101 ... 110, mounting type: snapped, for terminal block width: 8 mm, lettering field size: 5.15 x 8.15 mm, Number of individual labels: 10

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Marker for terminal blocks

Marker for terminal blocks - UC-TMF 8 - 0818137

<https://www.phoenixcontact.com/us/products/0818137>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 7.6 x 5.1 mm, Number of individual labels: 56

Marker for terminal blocks

Marker for terminal blocks - UC-TMF 8 CUS - 0824654

<https://www.phoenixcontact.com/us/products/0824654>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 8.2 mm, lettering field size: 7.6 x 5.1 mm, Number of individual labels: 56

Test disconnect terminal block - PTVME 6/S RD



1350427

<https://www.phoenixcontact.com/us/products/1350427>

Marker for terminal blocks

Marker for terminal blocks - UCT-TMF 8 - 0828748

<https://www.phoenixcontact.com/us/products/0828748>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 7.4 x 4.7 mm, Number of individual labels: 42

Marker for terminal blocks

Marker for terminal blocks - UCT-TMF 8 CUS - 0829672

<https://www.phoenixcontact.com/us/products/0829672>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 8.2 mm, lettering field size: 7.4 x 4.7 mm, Number of individual labels: 42

Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA

586 Fulling Mill Road

Middletown, PA 17057, United States

(+717) 944-1300

info@phoenixcon.com