

The display you are connecting must have an HDMI port that can accept a converted HDMI signal. Contact your display manufacturer to confirm it will work with a VGA + Audio to HDMI converter. If your display does not support this, an alternative solution is Tripp Lite's U244-001-HDMI-R USB to HDMI adapter.

VGA with Audio to HDMI Converter, Adapter for Stereo Audio and Video

MODEL NUMBER: **P116-000-HDMI**



Converts the VGA and Audio signal from a laptop or PC for use on a HDMI display

Description

Tripp Lite's P116-000-HDMI VGA + Audio to HDMI converter is the perfect solution for using your older laptop or PC with your new HDMI display. Simply connect your computers VGA and Audio ports to the converter, and the converter to the HDMI port on your display, and you are ready to go. No software or drivers required. If your computer has only a 3.5 mm. Mini Stereo Audio jack, connect it to the converter using a 3.5 mm. to RCA adapter cable such as Tripp Lite's P314-006. You can also convert the RGB Video and Stereo Audio signals on your DVD player, DVR, etc., for use on your HDMI display (Component Video to VGA adapter required) Furthermore, you reduce your equipment costs by eliminating the need to upgrade your computer's video card.

The P116-000-HDMI supports HD video resolutions up to 1080p, and computer video resolutions up to 1280 x 1024. Supports 24-bit True Color (8-bits per channel), and HDCP compliant.

Features

- Connect your VGA laptop or PC to a HDMI display to enjoy high definition video and audio
- Convert the RGB Video and Stereo Audio signals from your DVD player, DVR, etc., for use on a HDMI display (Component Video to VGA adapter required)
- Plug-and-Play, no software or drivers required
- Supports HD video resolutions up to 1080p, and computer video resolutions up to 1280 x 1024
- Supports 24-bit True Color (8 bits per channel)

Highlights

- Connect your VGA laptop or PC to a HDMI display to enjoy HD video and audio
- Convert RGB Video and Stereo Audio signals for use on a HDMI display
- Plug-and-play operation with no software required for easy, immediate installation
- Supports HD video resolutions up to 1080p, and computer video resolutions up to 1280 x 1024
- Reduce equipment cost by eliminating the need to update your computer's video card

System Requirements

- The display you are connecting must have a HDMI port that can accept a converted HDMI signal. Contact your display manufacturer to confirm that it will work with a VGA + Audio to HDMI converter. If your display does not support this, an alternative solution is Tripp Lite's U244-001-VGA-R USB to HDMI adapter.
- Computer with a VGA Video and 3.5 mm. or RCA Audio Jacks (If your computer has only a 3.5 mm. Mini Stereo Audio jack, you can use a 3.5 mm. to RCA adapter cable such as Tripp Lite's P314-006.
- DVD player, DVR, etc. with RGB Video and Stereo Audio jacks



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

- Reduce equipment cost by eliminating the need to update your computer's video card

(Component video to VGA
adapter required)

- **Supported PC Video**

Resolutions - 640 x 480 @
60Hz, 72Hz, 75Hz, 85Hz, 800 x
600 @ 56Hz, 60Hz, 72Hz,
75Hz, 85Hz, 1024 x 768 @
60Hz, 70Hz, 75Hz, 80Hz, 85Hz,
1280 x 1024 @ 60Hz, 75Hz

- **Supported HD Video**

Resolutions - 480i @ 60Hz,
480p @ 60Hz, 720p @ 60Hz,
1080i @ 60Hz, 1080p @ 60Hz

Package Includes

- P116-000-HDMI VGA + Audio to
HDMI Converter
- External Power Supply with
NEMA 1-15P Plug (Input: 100-
240V, 50/60Hz, 0.35A; Output:
5V, 2A, 4 ft.)
- Owner's Manual

Specifications

OVERVIEW	
UPC Code	037332180162
Technology	HDMI; VGA/SVGA; Stereo Audio
POWER	
External Power Supply Input Specs (V / Hz / A)	100-240V/ 50/60Hz/ 0.35A
External Power Supply Output Specs (V / A)	5V / 2A
External Power Supply Cord Length (ft.)	4.0
External Power Supply DC Barrel Connector Specs	OD: 5.5 x 2.1 x 10mm, Positive Pin, Negative Sleeve
PHYSICAL	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Color	Black
Shipping Dimensions (hwd / cm)	14.48 x 6.35 x 20.57
Shipping Dimensions (hwd / in.)	5.70 x 2.50 x 8.10
Shipping Weight (kg)	0.41
Shipping Weight (lbs.)	0.90
Unit Dimensions (hwd / cm)	3.18 x 8.89 x 6.99
Unit Dimensions (hwd / in.)	1.25 x 3.5 x 2.75
Unit Weight (kg)	0.18
Unit Weight (lbs.)	0.40
ENVIRONMENTAL	
Operating Temperature Range	32 to 158 F (0 to 70 C)
Storage Temperature Range	14 to 176 F (-10 to 80 C)
Operating Humidity Range	10 to 85% RH, Non-Condensing
Storage Humidity Range	5 to 90% RH, Non-Condensing
CONNECTIONS	
Side A - Connector 1	HD15 (FEMALE)
Side A - Connector 2	(2) RCA (FEMALE)
Side B - Connector 1	HDMI (FEMALE)
WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Tripp Lite:](#)

[P116-000-HDMI](#)