

D

C

B

A



D

C

B

A




GENERAL TOLERANCE					
DIM.RANGE	0 - 3	>3-6	>6-30	>30-120	>120-400
TOLERANCE	±0.1	±0.1	±0.2	±0.3	±0.5




CUSTOMER DRAWING




REVISION		
REV.	DESCRIPTION	DATE
A	INITIAL RELEASE	2020-08-25
B	ADD CODE NUMBER AND KEYWAY	2020/12/22
C	UPDATE SPECIFICATION	2021/1/5



DUST CAP ASSEMBLY VIEW



BUSBAR TYPE



SCREW TYPE

PART NUMBER: C10-765128- () () () ()

COLOR
PIN TYPE
KEYWAY
SEALING

CODE NUMBER: SLPHIRC() P() () ()

PIN TYPE
SEALING
KEYWAY
COLOR

ITEM	OPTION	PART NUMBER	CODE NUMBER
COLOR	ORANGE	0	O
	BLACK	1	B
	RED	2	R
PIN TYPE	BUSBAR	1	B
	SCREW	2	T
SEALING	IP67(MATED)	0	S
	UNSEALING	1	N
KEYWAY (Y°)	20°	1	1
	30°	2	2
	45°	3	3

TABLE 1	
KEYWAY(Y°)	KEYWAY CODE
20°	K1
30°	K2
45°	K3

SPECIFICATIONS	
CURRENT RATING	300A
VOLTAGE RATING	1500V DC
OPERATING TEMPERATURE (AMBIENT)	-40°C~125°C
CONTACT RESISTANCE	0.5mΩ MAX
PROTECTION CLASS	IP67(MATED)

3. DUST CAP SHOULD BE REMOVED BEFORE PLUG MATING IN.

2. IF CHOOSE UNSEALING TYPE, THERE WILL BE NO GASKET.

1. THE REFERENCED PRODUCT SHALL BE COMPLIANT TO RoHS DIRECTIVE.

NOTES:

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS FOR ANY PURPOSE OR USED FOR MANUFACTURING PURPOSES WITHOUT WRITTEN PERMISSION FROM THE AMPHENOL CORP.

UNLESS OTHERWISE SPECIFIED		APPROVALS		DATE
LINEAR DIMENSIONS ARE IN: MILLIMETERS TOLERANCES: ANGLES= ±2° DEFAULT LINEAR TOLERANCES SEE TABLE		PREPARED BY:	Yuexiang Zhang	Aug-26-20
		ENGINEER IN CHARGE:	Seven Xie	
		DESIGN MANAGER:	Rob Weng	
		PRODUCT GROUP:	C&I	
DIM. & TOL. PER ASME Y14.5M-1994; DRM PER MIL-DTL-31000; OTHER AMPHENOL STANDARDS: 9-3800		AIPG DIVISION:		
LEGENDS:		MATERIAL SPEC	PROCESS SPEC	
=FLAG NOTE CALL OUT REFERENCE		N/A	N/A	
THIRD ANGLE PROJECTION				

AMPHENOL INDUSTRIAL OPERATIONS

Amphenol Technology(Zhuhai)Co.,Ltd
No.63, Xingnan Road, Sanzao Town, Jinwan, Zhuhai, PRC

10.3MM SURLOK PLUS RECEPTACLE 1500V TYPE

SIZE	CAGE CODE	DOCUMENT NUMBER	REV
C	77820	10-765128	C
SCALE: 2:1		REF: 10-730191	SHEET 1 OF 1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

[SLPHIRCBPNB1](#) [SLPHIRCBPNB2](#) [SLPHIRCBPNO1](#) [SLPHIRCBPNO2](#) [SLPHIRCBPNR1](#) [SLPHIRCBPNR2](#)
[SLPHIRCBPSB1](#) [SLPHIRCBPSB2](#) [SLPHIRCBPSO1](#) [SLPHIRCBPSO2](#) [SLPHIRCBPSR1](#) [SLPHIRCBPSR2](#)
[SLPHIRCTPNB1](#) [SLPHIRCTPNB2](#) [SLPHIRCTPNO1](#) [SLPHIRCTPNO2](#) [SLPHIRCTPNR1](#) [SLPHIRCTPNR2](#)
[SLPHIRCTPSB1](#) [SLPHIRCTPSB2](#) [SLPHIRCTPSO1](#) [SLPHIRCTPSO2](#) [SLPHIRCTPSR1](#) [SLPHIRCTPSR2](#)